



# PRODUCTS 2020



## BedSide Cabinet



Model NO.: AG-BC006

Type: Locker

Feature: Easy Disinfection, Damp proof, Fireproof, Anti-Cross-Infection, Abrasion Resistant

Layer: 2 Layers

Size: 500X490X780mm, 14kg

Specification: 475\*475\*875mm

Material: Hard Plastic

Window: Without Glass Window

Certificate: CE & ISO

Advantage: High Strength Medical Cabinets

Origin: China

### **Product Descriptions:**

Adjustable One Door ABS Bedside Cabinet

### **Specifications:**

Made of one-shot molding ABS engineering hard plastic, One drawer, one dining board, one door, shoes shelf at bottom, Two tower hanger.

### **Advantages:**

Anti-aging, anti-rust, clean, durable, moth proof, recycling, environmental protection.



## Operation Table



Model NO.: YSOT-3008D

Trademark: YSENMED

Origin: China

Type: Operating Table

### **Feature:**

Head Control X-ray Compatible Portable Operating Table

The table and base both adopt high quality 304 stainless steel. Imported Y type sealing ring with good sealing performance and is durable.

Rotary brake device which is easy for moving operating table.

**Length:** 2050±50mm , Width: 480±20mm , Height:(750\_950)mm , ±50mm Forward: ≥30° backward: ≥25° Leftward≥20° , rightward≥20° Head board Fold upward≥45°

Fold downward≥90 , Leg board Fold downward≥90°

Waist board elevation ≥120mm

### **PRODUCT ADVANTAGE:**

1. Base is stainless steel
2. Table-board is stainless steel



**Infusion Pump:**



- Audible and visual alarm for occlusion, empty, low battery, end of infusion, door open, wrong setting, etc., which gain patents
- Compatible with any brands of infusion sets after correct calibration;
- Preset solution volume to greatly reduce the workload of nurse
- Work mode: ml/h and drop/min can switch freely;
- Three levels of occlusion: high, middle and low;
- Purge function;
- KVO (keep vein open) the rate is 3ml/h;
- Power Source: AC100---240V, 50/60Hz; Internal Battery;
- Automatically record the settings of last infusion;
- BYS820D can store 2000pcs of infusion records and it has a drug library.
- Function to remove bubbles in the tube fast.
- Function to handle fast speed and large volume(bolus)

Brand Name : Beyond  
 Place of Origin : China  
 Type: volumetric  
 Number of channels: 1-channel  
 Description:

- Unique audible and visual alarm, safe and reliable, gain patents.
- Compatible with any brand iv sets after correct calibration
- Work mode: ml/h and drop/min. can switch freely

Features:

- HD LCD Display, high capacity words, friendly user interface, dynamically display working status;

Technical Specifications:

Infusion Rate	0.1 ml/h-1200 ml/h (1 ml/h step)
Rate Accuracy	within +- 5% (after correct calibration)
Total Infusion Volume	0--9999.9ml
Alarms	End of injection, occlusion, door open, bubble in the tube, wrong setting, low batter, AC power

## Stethoscope:



It is used to detect and study heart, lung, stomach, and other sounds in adult humans, human fetuses, and animals. Using a stethoscope, the listener can hear normal and abnormal respiratory, cardiac, pleural, arterial, venous, uterine, fetal and intestinal sounds.

Deluxe stainless steel head , light copper binaural chest piece comes with non-chill ring, kind care patented soft Ear-tips with inner spring binaural tubing assembly special binaural design to suit ear structure foam box packing

Origin: China

- 1.28" overall length.
2. Traditional bell combined with a tunable diaphragm that allows the user to conveniently alternate between low- and high-frequency sounds without turning over the chestpiece.
3. Excellent acoustic seal and comfortable fit with patented 3M Littmann Snap Tight Soft-Sealing Eartips.
4. Comfortably angled, anatomically correct headset.
5. Patient-friendly, nonchill rim and diaphragm.
6. Single-lumen tubing is available in a variety of popular colors.
7. Latex free.



**Pulse Oximeter:**

- **Fast & Convenient Readings**

SpO2 and Pulse Rate are graphed on the bright LED display. The LED display cover prevents ambient light washout, making readings crisp and clear. Average time for a reading is 8~10 seconds.

- **One Size Fits All**

Accommodates pediatric to adult finger-sizes and can be used by sports and exercise enthusiasts. Easily and gently clamps onto a wide array of finger-sizes

- **No Strings Attached**

Being wireless means you have no restraints on when and where you want to take a measurement, perfect for outdoor activities! The included, 2 AAA batteries ensure continuous use for up to 32

hours minimizing downtime.

- **But That's Not All!**

Also includes lanyard, instruction manual, two AAA-batteries, and a convenient carrying case. Power consumption of the product is low and the two originally equipped AAA-batteries can be operated continuously for 24 hours.

**Main Features:**

- Digital LED display with low power consumption plus auto-power off feature allows for 40 continuous hours of battery life.
- Cover against ambient light offers superior ease of reading. Fast and accurate SpO2 and pulse measurements.
- Accommodates pediatric to adult finger sizes and can be used by sports and exercise enthusiasts as well as anyone interested in measuring pulse rate and oxygen saturation.
- Includes 2 AAA batteries, lanyard, and convenient carrying case.
- Guaranteed one year warranty offered exclusively.
- Pulse rate value display, bar graph display
- Pulse waveform display
- The display mode can be changed
- Screen brightness can be changed
- Low-voltage indication: low-voltage indicator appears before working abnormally which is due to low-voltage. Automatically power off function: when the device is under the state of measuring interface . it will automatically power off within 5 seconds if the finger falls out of probe
- Display format can be saved after power off



**Thermometer:**



**Main Features:**

- LCD display easy to read
- Measuring range from 32 °C to 42 °C (89.6 °F to 111.2 °F)

LCD Digital Thermometer

For Baby or Human Clinical Digital

Type:	Thermometer
Model Number:	Cassette
Thermometer	
Range:	32°C to 42 °C
Brand Name:	OEM
Name:	Digital Thermometer
Accuracy:	plus minus 0.1 centigrade
Place of Origin:	China (Mainland)
Usage:	Household
Response Time:	Around 1 minute or 30 seconds
Application:	Mouth
Certificate:	CE ISO
Display:	LCD Display





## Pen Light- Torch:



### Basic Info

Model NO.: SW-PL02

Lighting Period (H): >10

Light Range: <50m

Power Supply: Dry Battery

Material of Reflecting Cup: Glass

Bulb: Yellow

Bulb Type: Halogen Bulb

Charging Type: Battery

Surface Preparation of Reflecting Cup: Glass

Barrel Color: White Trademark: SUNNYWORLD

Origin: Wenzhou, China

Certification: ISO CE FDA

Material : aluminum

- SIZE: 13.5x1.25cm





**Electrocardiograph-ECG :****Main Features:**

- Detailed Product Description
- Single Channel ECG Machine
- Large screen display
- Simultaneously 12 leads acquisition

**Specification:**

Lead: Standard 12 Leads

Acquisition Mode: Simultaneously 12 leads acquisition

Record Mode: manual mode, auto mode1, auto mode2, auto mode3

Filter: AC filter; EMG filter

CMRR: >100dB (with filter)

Place of Origin: Guangdong, China (Mainland)

Brand Name: Jumper

Model Number: JPD-E01-L

Calibrating Voltage: 1mV±2%

Skin Voltage Tolerance: ±500mV

Time Constant: ≥3.2s

Frequency Response: 0.05~150Hz(-3dB)

Noise Level: below 15μVp-p

Sensitivity Threshold: ≤20μV Inter-channel Interference: ≤0.5mm

Paper Speed: 25,50mm/s(+/-

3%)Sensitivity: AUTO,2.5,5,10,20mm/mV

Recording System: Thermal-array System

Recording Paper Specifications: 63mmx30mm,Roll Paper

LCD: 192X64 LCD, Display waveform, Chinese and English menu and working status

Safety Standard: GB9706.1-1995, IEC class I, type CF

Power Supply: AC: 220V / 110V, 50/60Hz, 30VA

DC: 12V (1800mAh) rechargeable battery

Fuse Specification: AC time lag: T500mA/125V (110V) ;

T400mA /250V (220v);

DC time lag: T2A/250V; (110-230V);

Uses of ECG / EKG:

The electrocardiogram (ECG or EKG) is a noninvasive routine examination of the electrical activity of the heart that is used to reflect underlying heart conditions. Regular heart movements are controlled by a complex set of electrical impulses that direct the upper and lower heart chambers to contract and relax rhythmically.



**Patient Monitor:**



Model:800B  
Origin: China

**Features :**

- Advanced streamline outline design, compact, lightweight, in-built handle makes it truly portable
- Can be used to monitor adult, pediatric & neonate patient
- Low perfusion working possible
- Various display screen
- Large volume of tabular and graphic trends information storage and easy to recall
- Capture dynamic waveforms  
In-built Rechargeable battery which provides a backup time of up to 4 hours
- Intelligent audio and visual comprehensive alarm. Volume adjustment possible
- 12 " high resolution TFT LCD display

**Specifications:**

**ECG**

- \*lead mode;I,II,III,AVR,AVL,AVF,V
- \*Gain:X0.25,X0.5,X1,X2
- \*Heart Rate:15-300BPM(Adult)  
15-350BPM(Neonatal)
- Resolution:1 BPM
- Accuracy:+-1%
- \* ST measurement Range:-2.0-+2.0mV
- Accuracy:+-10%
- \*Pacemaker:Yes
- \*Sweep Speed:12.5 mm/s,25mm/s,50mm/s
- \*Bandwidth:Diagnostic:0.05--130Hz
- Monitor: 0.5--40Hz
- Surgery: 1-20Hz

**SPO2**

- \*Measure Range:0-100%
- \*Resolution:1%
- \*Pulse Rate:20-250BPM
- \*Resolution:1BPM
- \*Accuracy:+-3BPM

**RESP:**

- \*Measure Range:0-150BrPM
- \*Resolution:1BrPM
- \*Accuracy:+-2%

**Temp:**

- \*Measure Range:0-50C
- \*Resolution:0.1C
- \*Accuracy:+-0.1C

**NIBP:**

- \*Work mode:Manual,Automatic,Continuous
- \*Unit:mmHg,Kpa
- \*Measure Range:  
Adult: SYS: 40-280mmHg  
DIA: 10-225mmHg  
MEAN:20-240mmHg

**Pediatric:**

- SYS:40-220mmHg
- DIA: 10-160mmHg
- MEAN:20-170mmHg

**Neonatal:**

- SYS:40-135mmHg
- DIA:10-100mmHg
- MEAN:20-110mmHg
- \*Resolution:1mmHg
- \*Accuracy:+-5mmHg



## Wheelchair :



Made of PVC upholstery. It has seat width 41 & 46cm for choose.

### **Main Features:**

- Steel wheelchair
- Chromed steel frame, foldable chair.
- Fixed armrest and footrest, single cross bar, PVC upholstery.
- Aluminum foot plate

24" spoke solid rear wheel, 8" front castor

Model: SK-SW201

Power Supply: Manual

Dimension: L106xW65xH87cm

Seat width: 41cm/46cm

Load capacity: 100kg

Operated: Manual

Weight Capacity: 100kg

Specification: CE, ISO

Using Site: Hip

Trademark: Worldcare

Origin: Foshan China

### **Product Description:**

CE certificate economic manual Wheelchair (SK-SW201) This wheelchair is designed for people who can not walk easily by themselves. It is made of strong chromed steel frame, seat and back are



**Mayo Table:**



**Basic Info**

Model NO.: BSS031

Certificates: ISO,CE

Height: 76-126cm

Trademark: WANROOEMED

Origin: Jiangsu, China

Material: Stainless Steel

5PCS 2 Inch Castors: Yes

HS Code: 94029000

**Product Description:**

- BSS031 Double Bowl Stand
- Size:  $\phi$ 36\*76-126cm Made of stainless steel
- Height can adjust from 76-126CM,
- Double bowl, diameter: 36cm
- 5pcs 2 inch castors,2pcs with brake



## **Folding Screen:**



- The curtain is removable, attachable and washable.
- Frame: stainless steel material.
  - Screen is able to be used in narrow are, owing to foldable wings system if necessary.
  - The sections of the screen could be as customized. The size&color also as customized

### **Basic Info:**

Model NO.: O-3

Material: Stainless Steel

Suitable for: Patient

Specification: ISO9001 &ISO13485, CE.

Usage: Nursing Center, Office Treatment, Pharmacy, Sickroom, Patient Care

Feature: Easy Cleaning, Antimicrobial

Color: Blue

Trademark: XUHUA

Origin: Tianjin, China

### **Product Description:**

- Hospital Stainless Steel Mobile Screen (4-fold)
- Four winged screen is adjusted by castors.





### Weigh & Height Scale:



Mechanical Adult weighing scale / height weight scale  
Platform size: 38.5\*28cm Measure: 70cm--190cm

#### **Basic Info:**

Model NO.:ZZJKH-01  
Applicable Crowd:Adult  
Weight Range:8kg-200kg  
Function:Body Weight  
Power:None  
Shape:Polygon  
Certification:CE, ISO  
Appearance:Screen Printing Color  
Size:38.5\*28cm  
Trademark:SAINT FIRE  
Origin:Zhejiangyongkang, China

### **Product Description:**

160KG Mechanical height weight scale  
Platform size: 38.5\*28cm Measure: 70cm--190cm  
Capacity: 120kg/160kg



**Autoclave 18Liter:****18L Vertical Medical Autoclave:**

- 1.Safe and Auto-controlled
- 2.Disinfecting pail:0.018m<sup>3</sup>(280x260mm);
- 3.Working pressure:0.14-0.16Mpa;
- 4.power:1.5Kw

**Features:**

Valid of the disinfecting pail: 0.018m<sup>3</sup>( $\varnothing$ 280x260mm)  
Rated working pressure: 0.14-0.16Mpa  
Max.working pressure: 0.165Mpa  
Supply voltage: AC220V,50Hz  
N/G.W: 14/16kg  
Model No.: BJ3004-1  
Brand Name: YONGFENG  
Certificate: CE, ISO9001, 13485  
Function: MEDICAL STERILIZING

**Description:**

The sterilizer is a table type in safety and auto-controlled, which is designed for the unit of medical health, pharmacy, science and technology etc. And mostly suitable for sterilizing of surgical, dental and eye instruments, glassware medicine, culture medium and biological dressing, food and goods



### 4-eyes Portable Operation Lamp:



### **Product Description:**

- 1, Reliable quality, affordable price, sound service
- 2, CE & ISO approval

MT02005C04 Mobile Stand Operating Room OT Lights  
MT02005C04 luminescence shadowless lamp adopts light sources from different positions for focus to eliminate shadows of different parts of medical workers. Vertical mobile setup with braking device is not limited by the space of surgical room and is safe and reliable in use.

### **Basic Info:**

Model NO.: MT02005C04

Type of Operating Light: Single Operating Light, hoisted 4-reflector luminescence shadowless lamp

Place of Origin: Jiangsu,China (Mainland)

Type: Operating Light

Certification: CE, ISO13485

Item: Operating Lamp

Model Number: Mt02005c04

Technical Specification:

Illumination:  $\geq 50,000\text{LX}$  (at 1m distance)

Color temperature:  $4000\text{K} \pm 500\text{K}$

Mains voltage:  $\text{AC}220\text{V} \pm 10\%$  50Hz

Bulb voltage: AC24V Bulb power





**9-eyes Ceiling Operation Lamp:**

Hands and other parts caused. The illumination can be adjusted according to actual needs.

Technical Specifications:

Illumination	90000lux
Color rendering index	100≥Ra≥85
Total irradiance	≤600W/m <sup>2</sup>
	280-320cm

**Basic Info:**

Model NO.: MT02005C08

Type of Operating Light: Single Operating Light

Power Supply(AC): 220+\_10% 50Hz

Rated Voltage of Bulb: 24V

Depth of Light Beam: >=500mm

Origin: China

Certification: CE, ISO13485

Product Type: 9 reflector Luminescence Surgical Operation Lamp

Model Number: Mt02005c08

Color Temperature: 4000+\_500k

Rated Power of Bulb: 225W

**Introduction:**

9-Reflector Luminescence Surgical Operation Lamp use of multiple different sources,by focusing knob,so the beam is irradiated from different locations surgery,reduce the shadow medical staff head,



**Delivery Table:**

Delivery Table –Bed: made in 3 sections.

Size: 1680 × 620 × 800 mm.

Origin: China

**Description:**

With adjustable Back rest & leg rest to varying positions.

Framework made of Mild Steel Epoxy coated finish.

Supplied with S.S. bowl and two leg holders.

Mounted on protective stumps.

Freight saving knock-down construction.

Table frame made of steel tube, Pre-treated and epoxy ; Fixed

bases with protective plastic feet;

Adjustable three sections with independent controls

Bed top is high-density polyurethane foam, and covered with washable

faux leather: waterproof, flame retardant; Mattress thickness: 40mm; one

pair of adjustable knee support; one pair of handgrip; With a S.S bowl;

Load bearing: 150kg; Knock down construction





**Single Crank Manual Bed:**

**Quick Details:**



Specific Use: Hospital Bed  
Material: Metal  
Metal Type: Iron  
Folded: No  
Size: 2150\*950\*550mm single function manual bed  
Model Number: BT-AM303 medical one move bed  
Place of Origin: Jiangsu, China (Mainland)  
Castors:: Weight single function manual bed  
Motor:: Linak or Timotion single function manual bed  
Weight Capacity:: 200kg single function manual bed



**Double Crank Manual Bed:****Product Description :**

- Size:2080×980×(540-650)mm (With guardrail)
- Fourth-aluminum alloy side rails.
- Aluminum alloy hand-squeezed prevention guardrail, can be hidden to the bed surface.
- ABS bed head/foot board, detachable and easy-clean.
- Steel punching bed surface.
- Powder coated steel bed frame.
- 5 inch silent caster.diameter,125mm
- Backside can be folded 0-80. Knee side can be folded 0-40°.
- With over-bed table.
- With shoe rack.
- The height can be adjustable.

**Basic Info:**

Model NO.: DP-A203

Type: Manual Bed

Using Ambient: Hospital Bed

Certification: CE, ISO13485

Bed Surface Material: Steel Punching

Backside Folded Degree: 0-80°

Bed Frame Material: Powder Coated Steel

Size: 2150×900×500mm

Origin: Jiangsu, China

Folded: Folded

Numbers of Function: Two-function

Knee Side Folded Degree: 0-40°

Bed Head Material: ABS





**Stool:**



**Quick Details:**

Type: Hospital Furniture  
Material: Metal  
Size: 400\*500-660mm  
Model Number: AG-NS001 medical doctor Stool  
Color: Black medical doctor stool  
Service: Lifetime for medical doctor stool  
Type:: hospital furniture  
Metal Type: Iron  
Place of Origin: Jiangsu, China (Mainland)]  
Product Name: AG-NS001 medical stool black medical doctor stool used for doctors  
Folded: No  
Certificates: ISO13485,CE for medical doctor stool

**Specifications:**

H480~650mm by Gas Spring

Material:

The fabric is pressed PVC artificial leather and steel frame chromed.



**Instrument Trolley:**



**Description:**

It Applicable for carrying apparatus treating patient

- big Size : 500\*350\*1050mm
- small size: 670\*450\*900mm
- Stainless steel

**Quick Details:**

Specific Use:	Hospital Trolley
Material:	Metal
Metal Type:	Stainless Steel
Brand Name:	Saikang
Place of Origin:	Jiangsu, China (Mainland)
Model Number:	SKH001-2
Certificate:	CE & FDA & ISO9001 & ISO13485



## Ambulance Stretcher:



### **Quick Details:**

This type of stretcher is characterized by its light weight, safe usage and easy for sterilization.

Type: Ambulance Emergency Stretcher

Model Number: YXH-3B

Material: Aluminum Alloy & Foamed Cushion

Origin: China

Load Bearing: 159kg

Certificate: CE;FDA;ISO

Backrest: Can be lifted

### **Parameters of Ambulance Emergency Stretcher YXH-3B :**

- High Position (L x W x H ): 190 x 55 x 92cm
- Low Position (L x W x H ): 190 x 55 x 25cm
- Max. Angle of Backrest: 75°

### **Specification:**

Made of high strength aluminum alloy thick wall pipes.

Soft foamed cushion surface with adjustable backrest, making the wounded feel comfortable.

Easy to handle, one person is enough to send patient (with this stretcher) to the ambulance car.

Foldaway legs, controlled by the handles on both ends of the stretcher.

Fixing devices make the stretcher locked when on the ambulance car.



## Aluminum Stretcher:



### Quick Details:

Type: aluminum folding stretcher  
Place of Origin: Jiangsu, China (Mainland)  
Model Number: YJK-F1-1 aluminum folding stretcher  
Material: aluminum alloy  
Certificates: CE,FDA  
Bearing: 159KG

### Technical features:

Product Size (L\*W\*H): 208\*55\*13cm  
Folding size (L\*W\*H): 104\*17\*9cm

### Description for aluminum folding stretcher :

It is made of high strength aluminum alloy material and the waterproof leather materials. It has characterizes of light-weighted, small-sized, easy-carried, reliable quality, use-safely and easy for sterilization, etc. It is commonly used in hospital, gymnasium, ambulance, and battle fields to carry patients and wounded person.





**Infusion Stand:****Quick Details:****Description:**

IV pole, also called IV stand, drip stand, infusion pole or infusion stand is often placed beside or installed on hospital furniture for easy IV infusion. At Medcare, we offer two types of stainless steel IV poles.

They are designed with 4 or 5 feet, and each foot is equipped with a caster for easy movement. Each of our IV stands can simultaneously hold 4 bottles. Main stand is made of stainless steel and enables height adjustment as your needs. For various hospitals and private clinics, our IV poles can be an optimal choice

Model: MT-IV2 IV Pole stand

Origin: China

Size: 550\*550\*1320-2350mm

Folded: No

Material: Metal(stainless steel) or plastic

OEM: Available for medical drip stand

Special use: Hospital use

Castors: with brakes

Height: adjustable

Certification: CE&ISO

Quality: High quality



**ENT Set:****Product Description:****Otoscope:**

View the tympanic membrane and external ear canal to diagnose outer and middle ear pathologies.

**Ophthalmoscope:**

Aperture with large circle for examination of the fundus of the eye.

- Focusing wheel with corrective lenses
- Nasal speculum expandable
- Bent arm illuminator
- 2 laryngeal mirrors No. 3 and 4
- Tongue blade holder
- Battery handle with Plug-in connector for fast and secure attachment, with switch for luminance adjustment
- Durable and sturdy metal head for long service life.
- Head and Handel made of chrome-plated brass.

- Simple exchange of the lamp at the base of the instrument head. In hard protective deluxe case with sturdy sliding safety catches.

**Technical Parameter :**

With 2.5 V halogen lamp, similar to daylight, adjustable luminance.  
Swiveling viewing window with 1X-2x magnification  
Contain 3 reusable metal aural specula of 2.4, 3.2 and 4mm

**Diaper compensation:**

0 +0.5 ±1 +1.5 ±2 ±3 ±4 ±5 ±6 ±8 ±10 +12 ±15 ±20

2 x "Type C" Batteries, approximately 10 hours continue working time

**Basic Info:**

Model NO.: MN-5510-1

Certification: CE, FDA, ISO13485

Medical Devices Reg./Record No.: Ceno.02312

Specification: ISO CE FDA

HS Code: 9018909000

Classification: Biological Diagnostics

Group: Adult & Children

Material: Aluminum

Origin: Zhejiang, China



## Syringe Pump:



### Features:

- Syringe pump has human voice alarm function, which only available from us
- Freely Stackable: Users can freely stack one syringe pump onto another to provide multiple Solutions, which is very useful in clinical treatment. It can stack eight pumps
- The syringe pump can set three grades occlusion: High, medium and low
- HD LCD Display, Dynamically display working status 5.
- Syringe pump will automatically open up KVO once injection is finished
- The syringe pump is compatible with 10ml, 20ml, 30ml, 50 /60ml syringe of any brands

KVO rate	1ml/h
Operating power	AC100~240.0V, 50/60Hz, Power:≤30VA Internal rechargeable battery: DC
Operating environment	temperature:+5~+40°C,
Storing environment	temperature:-30°C~+55,
Atmospheric pressure	860hPa~1060hPa
Safety level	Class II with insulated enclosure, internal power supply, BF-type continuous normal running equipment.
Dimensions	280(L)×210(W)×130(H)(mm)

### Description:

The BYZ-810 single channel syringe pump from Byond is freely stackable, where users can stack one syringe pump onto another to provide multiple solutions. It is compatible with any brand of syringes. It has three unique working modes, such as rate mode, time-volume mode and dosage-weight mode, and has KVO and Bolus functions. It has a human voice alarm system and an accurate injection rate that make the injection process safer.



**Blood Bank 120 liter:**

Model NO.: A13.02120  
 Door Number: Single Door  
 Power Source: Electricity  
 Temperature Type: Double-temperature  
 Certification: CE, ISO  
 Voltage: 220V/50Hz  
 Weight: 60kg  
 Origin: China  
 Capacity: 101-200L  
 Function: Cold Storage & Freezing  
 Total Useful Volume: 120L  
 Input Power: 180W  
 Exterior Size (Width\*Depth\*Height): 500×500×1260  
 Layers: 4

**Product Description:**

- Precise temperature control system  
 The worldwide famous high-accuracy computer-controlled temperature system with original binding can maintain the temperature constancy in the box at 2~8°C precisely. The temperature set-value can be adjusted at 0°C~14°C, and the temperature display precision is 0.1°C, the resolution is 0.1°C and the adjusting increment is 0.1°C.

- Safe control system  
 Keyboard lock, password protection function, and method against missing-adjustment of the operating parameter; Setting of the alarm temperature range. 7 system failure alarms (high temperature alarm, low temperature alarm, sensors failure alarm, door-opening alarm, electricity failure alarm, low back-up battery alarm, low voltage alarm).
- Refrigeration system  
 Import and adopt the original binding Germany DANFOSS high-performance compressor; Import and adopt the original binding "Bi-Sonic" double fan strongly against the low temperature and moisture
- Humanization design  
 High-quality adjustable stand of plastic coated steel wire can make the operation and the cleaning easily. The large-screen design is easy for observation. The safe lock design can prevent missing-opening. The refrigerator body is made of high-quality structural steel plate, Double transparent insulation glazed door, filled with inert gas. The power saving lamps on the body can light the whole space inside the refrigerator.
- 24-hours tracing, recording and printing systemOptional  
 The imported temperature recording and printing system. There are four precise temperature sensors (two sensors for some systems) inside the box and two temperature indicators outside the box, which are to display the temperature of upper and lower point, for users to supervise the temperature at each operating states in the box.



**Fetal Doppler:****Description :**

- LCD display with back light;
- Real time measurement;
- 4 different display modes;
- Automatic power-off when detects no-signal for 20 seconds;
- Battery status and voice volume indicator;
- Detachable sensor probe with 2.0 MHz in continuous waveform;
- Probe protection compartment;
- Built-in speaker with adjustable volume;
- Built-in rechargeable battery and AC re-charger;
- Ultrasonic couplant provided

**Basic Info:**

Model:DS120A

Origin: China

Characteristics :

Applications: fetal

Ergonomics: pocket

Options and accessories: with heart rate monitor

**Technical specifications:**

Power Supply: Built in rechargeable battery

Working voltage 7.4V > 5 hours operating time AC recharger

Frequency:

2.0 MHz continual wave Intensity < 2mW/cm<sup>2</sup> of 2.0MHz P:< 0.35MPa

Measurement accuracy:±1% or ±1BPM

Safety

The whole process of design, material purchase and production is in compliance with the CE standard

Precision

Special HR self correlation reading algorithm and continuous working method to ensure correct and reliable fetal heart rate (FHR)

measurement

Artistic Outlook

Compact, streamline and portable design

Durability

The precise production process and expert craftsmanship with ISO 13485 quality management ensures the longevity of this product

LCD Display Dimension:

39x27mm

Speaker Power 1W

Dimension:

Length:15Cm

Width:10 Cm

Depth:4Cm

Weight:300Gram

Equipment Supply:

Main Unit with LCD Display

Transducer Fetal Doppler

Battery Rechargeable



## Ultrasound Trolley:



Function: Anti-Bacterial, Dust-Proof

### Parameters about Trolley:

- Length: 783.05mm
- Width: 407.82mm
- Height: 800.08mm
- ABS Plastic Mobile Trolley for Ultrasound image scanner 30 inch (75cm) high, 16 wide (40cm), 28 inch deep (70cm) with handle, 26 inch deep without handle
- Median Shelf for printer, Low shelf for UPS or other
- 4 big wheeling with 2 breaks, easy to assembly probe and ultrasound gel holder

### Product Description:

This Trolley is specially designed for PORTABLE ultrasound machine, ECG machine and other Medical Device  
Full protection to ultrasound machine, probes, video printer, etc.  
Made of ABS, strong & light weight  
With Wheel-brake, easy to move and stop anywhere at any time



**Infusion Stand Plus:**

Metal Type: Stainless Steel

Folded: No

Size: 1520-1950(mm)

Place of Origin: , China

Brand Name: LH

Model Number: OEM

Product name: IV Stand with 4 Hooks

Feature: Height Adjustable, Rolling

Hook: 4 hooks at top

Specific Use: Hospital Dividers

**Product Description**

1.The iv pole Whole frame made of stainless steel.

2.Stainless steel hospital I.V pole,drip stand.

3.Medical I.V stand.

4.Hospital I.V pole,drip stand with CE and ISO Certificates.

5.5 Casters and Height adjustable.

Iv stand with Short, No-Tip Wheelbase

Includes 4 hooks

Base has 5 legs

3" rubber ball bearing casters

Base crafted from epoxy-coated steel

Adjust height with one hand with easy-to-use knob

General Use: Commercial Furniture

Type: Hospital Furniture

Material: Metal



**Infrared Thermometer:**



Place of Origin: China  
 Model Number: LX-314  
 Power Source: Power Supply  
 Mode: Removable Battery  
 Application: Forehead  
 Material: Plastic  
 Instrument classification: Class II  
 Product name: Digital Infrared Thermometer  
 Function: Body temperature measurement  
 Size: 148\*87\*43CM  
 Net weight: 113g  
 Box: Customizable  
 Power supply: 3V DC (2 "AAA" Batteries)  
 Memory: 32 Sets  
 Measurement range: Body 32-42.9°C  
 Safety standard: GB/T 21417.1-2007

infrared thermometer	Infrared thermometer
Model	LX-314
Working temperature	16°C~32°C
Operating humidity Relative humidity	≤85%
Transportation and storage temperature	0°C~55°C
Transportation and storage humidity Relative humidity	≤85%
Atmospheric pressure	70KPa~106KPa



**Baby Warmer (David):**

Place of Origin: Zhejiang, China  
 Brand Name: DAVID Infant warmer equipment  
 Model Number: HKN-93 Infant warmer equipment  
 Instrument classification: Class II  
 Material: Stainless steel, rubber, ABS  
 Usag: Premature infant, delivery room, NICU  
 Size: 1270mm x 810mm x 1120mm  
 Market: Overseas market  
 Color: White

**Specification :**

Power requirement: AC220V-230V/50Hz or AC110-120V/50-60Hz, 700VA  
 Control Mode: Pre-warm Mode, Manual Mode and Baby Mode are controlled by micro-computer Baby Mode temperature control range: 34.5°C-37.5°C  
 Skin temperature display range: 5-65  
 Accuracy of skin temperature sensor:  $\pm 0.2$   
 Temperature uniformity of mattress:  $\leq 2$   
 Angle of heater head: 0°, 30°, 60° for two ways  
 Inclination of the bassinet:  $\pm 10^\circ$   
 APGAR timer: audible and visible alarm when the device runs to 50''~1', 4'50''~5', 9'50''~10'  
 Failure alarm: over temperature alarm, deviation alarm, sensor failure alarm, power failure alarm, setting alarm, checking alarm and so on.  
 Dominant wavelength of blue light: 400-550nm  
 Environmental Requirement  
 Operating range: 18~30  
 Ambient air velocity rate:  $< 0.3$  m/s  
 Product Packaging  
 Package: The whole unit is packed into one carton  
 Dimension: 1270mm x 810mm x 1120mm  
 Gross Weight: 110kg

Product advantage: Three control Modes: Pre-warm Mode, Manual Mode and Baby Mode control by micro-computer;  
 Set Temperature and Baby Temperature can be displayed separately;

## WaterBath



### Quick Details

Classification: Laboratory Thermostatic Devices

Brand Name: xiangtian

Model Number: HH-S2

Place of Origin: China

Power Supply: AC 220V/110V 50Hz/60Hz

Temperature Range: RT~100°C

Power: 600W

Material: Stainless Steel

Hole Count: Double

## Product Description

### HH-S2 Digital Thermostatic Two-hole Laboratory Water Bath

Digital thermostatic water bath is widely used in concentrated solution, distillation, dipping in chemical reagents, drugs and biologics. Microcomputer control temperature system, digital display and liner using stainless steel making.

1 studio materials stainless steel water tanks, has a superior corrosion resistance.

2 high precision temperature control, digital display, automatic temperature control.

3 easy operation, use safety.

Power supply	220V 50HZ 110V 60HZ
Heating Power	600W
Temperature Range	RT-100°C
Temperature Control Accuracy	±0.5°C
Inner Dimension	300x150x150mm



**Oxygen Concentrator 5 liter**

Place of Origin: Jiangsu, China  
 Brand Name: YUwell  
 Model Number: 7F-5  
 Instrument classification: Class II  
 Flow Range: 0.5~ 5L /min  
 Oxygen Concentration: 95.5%~87%  
 Maximum Outlet Pressure: 40~ 70kPa  
 Sound Level: 55 dB (A)  
 Input Power: 500 VA  
 N.W.: 27kg (59.5 lbs)

Dimension: 44.5\*37.2\*68(cm)  
 Minimum Operating Time: 30minutes

**Features**

Complete plastic outer shell, safe and reliable.  
 Timing accumulating function, showing total working hours through the display screen. Press safety valve help ensure better security. With power failure alarm function. With pressure, cycle failure alarm, compressor failure alarm, low oxygen concentration alarm function. Compressor has got heat protection that ensures the safety of the compressor and concentrator. Colors currently available: Beige, Black

Flow Range	0.5~ 5L /min
Oxygen Concentration	95.5%~87%
Maximum Outlet Pressur	40~ 70kPa
Sound Level	55 dB (A)
Input Power	500 VA
N.W.	27kg (59.5 lbs)
Dimension	44.5×37.2×68(cm)
Minimum Operating Time	30minutes



## Oxygen Concentrator 7 liter



Place of Origin: China  
Brand Name: Medsinglong  
Model Number: 7F  
Instrument classification: Class III  
Product name: Medical Oxygen Concentrator  
Model: 7F  
Certificate: CE ISO  
Feature: 1 ~ 7 L / min  
Power supply: 110/220V 60/50Hz  
Weight: 17 Kgs

YUWELL Medical Oxygen Concentrator

Dimension: 480\*380\*620 mm

Oxygen Concentrator (Blue) A Flow:3LPM

Purity: 93%  $\pm$ 3%

Machine Dimension: 400\*300\*510mm

Carton Dimension: 480\*380\*620mm NW:14.8kg

GW: 17kg

Voltage: 220V/50HZ

Noise: <45dBA

Pressure: 40~60kPa

Power: 300W (Aver)

Product details

Adjustment range :1 ~ 7 L / min

Running noise: $\leq$ 60dB (A)

Timer error: $\leq \pm$  3%

Input power:150W



**Oxygen Concentrator 10 liter**

Oxygen concentration	95.5%~87%
Output pressure	40-70kPa
Pressure relief mechanism operational at	250kPa±25kPa
Operation noise level	≤60dB(A)
Input power	850VA
Minimum operating time	30 min

**Features**

- about this Yuwell oxygen concentrator
- Complete plastic outer shell, safe and reliable.
- Timing accumulating function, showing total working hours through the display screen.
- Press safety valve help ensure better security.
- Power failure alarming function, high pressure and low pressure alarming function.
- Compressor has got heat protection that ensures the safety of the compressor and concentrator.
- Having nebulizing interface optional.
- May connect with nebulizer to have nebulizing cure.

**Specification**

Place of Origin: China

Brand Name: Yuwell

Instrument classification: Class I

Name: 10L oxygen concentrator

Oxygen flow

0.5~10L/min



**Oxygen Concentrator 8 liter**

Place of Origin: China

Brand Name: Yuwell

Model Number: 7F-8

Instrument classification: Class I

Name: 8L oxygen concentrator

Flow Range: 1~8L/min NOTE: total flux 8L/min

Oxygen Concentration: 95.5%~87%

Maximum Outlet Pressure: 40kPa~70kPa (5.8psi~10.2psi)

Pressure Relief Mechanism Operational at: 250kPa±25kPa

(36.25psi±3.63psi)

Sound Level: ≤55dB(A)

Power Supply: AC120V±10% AC220V±10% AC230V±10% 50Hz 60Hz

4.6amps(AC120V)

Input Power: 500VA

Weight: 29kg

**Product Overviews**

1. Flow Range: 1~8L/min NOTE: total flux 8L/min, for two patients use at same time.
2. Oxygen Concentration: 95.5%~87%
3. Maximum Outlet Pressure: 40kPa~70kPa (5.8psi~10.2psi)
4. Pressure Relief Mechanism Operational at: 250kPa±25kPa (36.25psi±3.63psi)
5. Altitude: Up to 1230 meters (4000 ft) above sea level without degradation of concentration levels. From 1230 meters (4000 ft) to 4000meters (13129 ft) below 90% efficiency.
6. Sound Level: ≤55dB(A)
7. Power Supply: AC120V±10% AC220V±10% AC230V±10% 50Hz 60Hz 4.6amps(AC120V); 2.2amps(AC220V~240V)
8. Input Power: 500VA
9. Weight: 29kg



**Suction Machine one Bottle:**



Place of Origin: China  
Brand Name: Yuwell  
Model Number: 7E-A  
Warranty: NONE  
Instrument classification: Class II  
Name: Yuwell Sputum Aspirator 7e-a Portable Household Phlegm Suction Unit  
noise:  $\leq 65\text{dB(A)}$   
size: 35\*26.5\*28.5cm  
net weight: 5.5kg  
carton size: 45\*27\*35cm  
Input power: 90VA  
capacity: 1000ml





**Walker:**



**Product Description**

Single push button,easy to operate;

Arm pad,Hand grip and tip:Rubber, Latex Free.

Height adjustable;

Weight Capacity: 135kg.



Properties: Rehabilitation Therapy Supplies  
Place of Origin: Hebei, China  
Brand Name: LH  
Model Number: OEM  
Type: Handicapped Scooters, Extension Telescopic Pole  
Color: Silver  
Material: Stainless steel  
Product name: Wheeled walker  
Feature: Versatility  
Weight: 2400g  
Usage: Outdoor  
Tip: Pulley





**Oxygen Mask:**



**Features:**

- The turn-up rim can ensure comfortable fit with good seal
- Offered with head strap and adjustable nose clip
- The standard length of tube is 2.1m, and different length is available
- Available with CE, ISO, FDA certificates.

medical grade latex material

- with adjustable nose clip
- with elastic strap
- size m,l
- with 2m tubing

Place of Origin: China

Model Number: S,M,L,XL

Material: Plastic, Medical Grade PVC

Shelf Life: 3 years

Instrument classification: Class I

Name: Disposable Medical oxygen mask

Properties: Medical Polymer Materials & Products

Type: General Medical Supplies

Size: S M L XL

Feature: Eco-friendly

Application: Clinic,Hospital,Home



**Nebulizer Mask:**



**Features:**

- The turn-up rim can ensure comfortable fit with good seal
- Offered with head strap and adjustable nose clip
- The standard length of tube is 2.1m, and different length is available
- medical grade latex material
- with adjustable nose clip
- with elastic strap
- size m,l

**Quick Details**

Place of Origin: Jiangsu, China

Model Number:

S, M, L, XL, S, M, L, XL

Disinfecting Type: Ultrasonic

Properties: Medical Materials & Accessories

Size: S, M, L, XL, S, M, L, XL

Shelf Life: 3 years

Material: PVC, PVC

Quality Certification: ce

Instrument classification: Class I

Safety standard: EN 149 -2001+A1-2009

Product name: Medical Single use Disposable PVC

Application: Clinic,Hospital,Home



## Handheld Pulse Oximeter:



Model NO.FM-6520

Features: Dual Color OLED Display

Display Area: 56mm\*36mm

Trademark: FULLMEDI

Transport: PackageBox

Specification: 120\*63\*32mm

Origin: China

### **Feature:**

The monitor is a non-invasive, handheld patient monitor. It operates only on Common 1.5V AA alkaline or rechargeable battery power. It is compact, small, light, and easy for learning and handling. It is suitable for monitoring adult, pediatric, infant and neonate patients. It is widely used in the hospital's operation room, ICU, clinic section office, out-patient department, sickroom, emergency treatment, and the recovery and health care organizations, or in the family nursing and in the process of transporting patients. It can also apply to animals selectively. Parameters measured by the monitor include: arterial oxygen saturation (SpO<sub>2</sub>), pulse rate (PR), pulse strength. The monitor measures these parameters through a SpO<sub>2</sub> sensor and displays them on the LED screen after certain further processing.

The monitor is operated and controlled by the buttons on the front panel. It adopts LED in displaying measurements and in supplementary status indication.

The monitor has the following functions:

\*Measuring: Display of SpO<sub>2</sub>, PR and pulse strength.

\*Prompting: Battery capacity.

\*Alarm: Judgment of exceeding the limits, Audio and visual alarm.

\*Power saving: Automatic shutdown when no monitoring.

Net Weight: 0.13kg

Gross Weight: 0.8kg

Package Size: 210x160x70mm

Color: Yellow or Blue can be selected



**Autoclave 50 Liter:****Quick Details**

Type: Pressure Steam Sterilization Equipments

Brand Name: JIBIMED

Model Number: LS-50HJ

Place of Origin: Jiangsu, China

Material: Fully Stainless Steel Structure

Working pressure: 0.22MPa

Max Working Pressure: 0.23 Mpa Automatic Sterilization

Heat average:  $\pm 1^{\circ}\text{C}$

Working temperature: 134 Degrees Celsius

Timer: 0~60min

Certificates: ISO

**Product Application**

It is installed with an electrical heater, an automatically pressure-temperature controller, a safety valve, a releasing valve, a pressure-temperature indicator, an alarm bell for finished sterilization and instrument to automatically cut off the power of the heater. It has the advantages of effective sterilization, convenient operation, safe, less electric city consuming and cheap. It is ideal equipment for clinics, scientific research institutes and other organizations to sterilize surgical instruments, fabric, glassed, culture media etc.

**Main Features**

1. Fully stainless steel structure
2. Hand wheel type of quick-open door structure
3. Door safety lock system
4. Digital display of working status, touch of key
5. Auto discharge the cool air, and steam discharging automatically after sterilization
6. Over temperature & over pressure auto-protection
7. Safe protection of water lacking
8. Self-inflating type seal
9. Automatically shut off with beep reminding after sterilization
10. Used for sterilization of medical instruments, medical cotton products.
11. Fully stainless steel SUS304/AISI 304 -3mm



**Autoclave 100 Liter:**

Model NO.MED-B100L  
 Sterilization Information Recording and Printing  
 Material:Stainless Steel  
 Autoclave 100L  
 Autoclave Steam Sterilizer  
 Sterilizzatrice Autoclave 100 L  
 Guangdong, China (Mainland)  
 Sterilizzatrice Autoclave Per Alimenti 10.22MPa  
 Working Temperature: 134oc  
 Heat Average <1oc  
 Adjustment of Temperature0~134oc  
 Temperature Scope105~134oc  
 Max Working Pressure0.23 MPa  
 Timer Scope0~60min

**Characteristics of our autoclave sterilizer**

1. Indicator light indicates working state
2. Over-temperature & over-pressure auto-protection device
3. Double scale indication pressure gauge
4. Safe protection of water lacking
5. With the below exhaust structure,which is convenient to exhaust the cold air
6. Automatically shut off with beep reminding after sterilization
7. Fully stainless steel structure
8. Easy to operate,safe and reliable
9. With two stainless steel sterilizing baskets

**Application of our autoclave machine**

The Vertical Cylindrical Pressure Steam Sterilizer is installed with an electrical heater, an automatically pressure-temperature controller, a safety valve, a releasing valve, a pressure-temperature indicator, an alarm bell for finished sterilization and an instrument to automatically cut off the power of heater. It has the advantages of effective sterilization, convenient operation, safe, less electro city consuming and cheap. It is ideal equipment for clinics, scientific research institutes and other organizations to sterilizer surgical instruments, fabrics, glasses, culture media etc.



**Drug Trolley:**

Model Number: KY- CH8132-75RB

Brand Name: kenyue

Origin: China (mainland)

**Key Specifications/Special Features:****Product Description:**

1. Structure: two small pumps, two middle pumps, one large pumps, aluminum alloy column, infusion stand, defibrillator platform, stainless steel guardrail, sharp box.
2. Left side: sub-workbench, right side of data box.
3. Right side: 2 Pink dirt buckets.
4. Back: Power supply, defibrillator, oxygen cylinder bracket.

**Advantage:**

1. Good product quality
2. Manufacturer directly supplies products

**Product application scenario:**

1. hospital
2. clinic
3. icu



**Drying Oven:****Quick Details**

Type: DRYING OVEN

Model Number: DHG-9123A

Place of Origin: Shaanxi, China

Brand Name: TOPTION

Voltage: 220V

Power: 2kw

Dimension(L\*W\*H): 1380\*1200\*2000

Certification: ISO9001

Name: DHG-9123A Blast Drying Oven / Lab Drying Machine

Temp range: RT+10°C~250°C

Working room size (mm): 550\*350\*550

Application: Drying Oven

Product name: Drying Oven

Material: 304 Stainless Steel

Color: White

Capacity: 20-1000L

Heating source: Electricity

Installation: Guided

Weight: 100kg

Main description of TOPTION DHG-9123A Blast Drying Oven / Lab Drying Machine

1. Digital display
2. Micro-computer controlling, with timing function.
3. Timing range: 1~9999 min
4. Double glass observation window, the wind of inlet and outlet can be adjusted, stainless steel liner.
5. Corners arc-shaped design



**Baby Incubator (David):****INFANT INCUBATOR**

Model No:	YP-100
Temp. range	25~37°C
Temp. variability	≤0.5°C
Temp. uniformity	≤0.8°C
Noise inside hood	≤55dB(A)

Air mode control;

- Set temperature and air temperature are displayed separately;
- Natural air flow humidity;
- Multiple failure alarm indications;
- RS-232 connector;
- Low noise DC motor;
- Skin temperature control system as optional.

**Alarming:**

Audible and visible alarm indication, and it can indicate the real temperature and cut off the power supply of heater (except for the low deviation alarm), meanwhile, the skin temperature indication window can indicate the alarm code. For the alarm 1-6, the relevant light is on, and for the alarm 7, all alarming lights are on; All alarm sound can be cancelled except for the power failure alarm and the system alarm.

Over-temp alarm: When the temperature ≤ 38° C;

Upper Deviation alarm: Air temperature control 3.0° C

Lower Deviation alarm: Air temperature control -3.0° C

Sensor alarm: When the sensor is disconnected, open circuit, short circuit or put on the wrong place;

Fan alarm: When the fan is blocked, speed ≤ 1000rpm or stop working;

Power failure alarm: When there is no power or the power cord is disconnected.





**Phototherapy:**

Model NO.JRB-100 (LED)  
 Power Supply 220/110V, 50/60Hz  
 Trademark JoRadaint  
 Transport Package Cartons  
 Specification 96cm× 52cm× 26cm  
 Origin P. R. China

**STANDARD COMPOSITION:**

Use blue tube or LED as light source;  
 LED Digital Timer, display therapy time & total time;  
 Lifting & Mobile Stand, radiant head rotating by angle of 30°/ 60° /90°.

**TECHNICAL SPECIFICATIONS:**

Input power: <150VA  
 Light source: Blue tube/ LED tube  
 Light source effective life: 2,000 /50,000 hours  
 Wavelength: 400-550nm  
 Luminosity:  $\geq 4300\text{Lux}$  at distance of 40cm  
 Irradiance treatment distance: 35cm  
 Effective area: 45cm×24cm  
 Bilirubin total irradiance maximum (Ebi max):  $\geq 2000\mu\text{W}/\text{cm}^2$   
 Ebi in effective area surface:  $\geq 500\mu\text{W}/\text{cm}^2$   
 Ebi average in effective area surface:  $\geq 400\mu\text{W}/\text{cm}^2$   
 Uniformity of Ebi: >0.4  
 Infrared radiation in effective area:  $\leq 10\text{mW}/\text{cm}^2$  (760nm< $\lambda$ ≤1400nm)  
 Ultraviolet radiation in effective area:  $\leq 1.0 \times 10^{-5}\text{mW}/\text{cm}^2$   
 (180nm< $\lambda$ ≤400nm)  
 Time display accuracy: 2h±1min  
 Operate noise:  $\leq 55\text{dB(A)}$  (ambient noise is lower than 40dB(A))  
 Basic performance: the equipment total irradiance (Ebi)  $\geq 500\mu\text{W}/\text{cm}^2$ .  
 Time display range: 9999h 59min  
 Adjust angle: 30°, 60°, 90°  
 Adjust height: 1100mm~1500mm



## Overbed Table



Model NO.Overbed Table  
 Trademarkcustomized  
 SpecificationISO CE  
 OriginChina  
 HS Code9506911900

Adjustable Steel Medical Hospital Overbed Table is Designed for high usage situations, such as hospitals, care homes and private nursing homes,The table can be easily lifted without having to operate the control handle and will remain at the position required with no further adjustments and can only be lowered by operating the control handle.

### Features

1. surface Phenolic compact laminate (HPL) material table surface design
- 2.The column adopts the aluminum profile with electrostatic spraying, give oxidation treatment after matural aging.
- 3.Lift control by gas-springs.
- 4.The table height can be adjusted easily, no complicated switch.
5. 360° rotation angle, any angle can be fixed for reading
- 6.Castors two with brakes
- 7.Smooth,quite operation

Table top Size: L890mm x W440mmx Thickness30mm  
 Overall Size: L890mm x W440mmx H760-1150  
 Color: Light Grey, Natural Beech, Antique Oak, Royal Maple



## Mobile Inspection Lamp



Model NO.BT-202B-8  
Sample Available  
User's Manual Available  
Service Manual Available  
Transport Package Carton  
Origin China  
HS Code 9405409000

21W LED Mobile Examination Light/Inspection lamp

### **Technical parameters:**

Voltage:	AC90-240V 50-60Hz
Input power:	≤50VA
Bulb power:	LED 7 x 3W
Color temperature:	5500±500K
Life of bulb:	50000h
Illumination:	50000Lx
N.W.:	7.5 KGS.
Packaging by carton	845 x 215 x 155 mm

### **Feature:**

1. Professional appearance design, high-end and classy.
2. Big handle, switch front, more humane.
3. LED lighting, sunlight color, no temperature rise.
4. Hose flexible, multi-angle lighting.



## Examination Lamp



### Features and Benefits

- 16" flexible goose neck arm adjusts 360 degrees
- 3-prong plug
- Adjustable height: 48" - 72"
- For use with incandescent light bulbs up to 60 watts
- Goose-style neck allows the lamp to be adjusted in any direction
- UL listed
- Weighted, steel base prevents tipping

Flexible gooseneck stainless steel examination light is mobile, 16" flexible goose-neck lamp with dome-style shade by Drive Medical can be adjusted in any direction thanks to an arm that adjusts a full 360 degrees. The height can be formed to suit your needs as well, adjusting anywhere from 48" to 72". This model also includes four casters that allow for mobility whenever and to wherever necessary. The lamp includes a 3-prong plug, is UL listed and is for use with incandescent light bulbs up to 60 watts.

### Product Specifications

- Adjustable Height: 48"-72"
- Product Dimensions: 4.00"(L) x 4.00"(W) x 48.00"(H)
- Warranty: Limited Lifetime
- Weight 10.00 lbs
- Color Chrome
- Assembly Basic Assembly Required
- Installation No Installation Required
- Material Steel
- Exam Lamp Dome Style Shade
- 16" flexible goose neck arm adjusts 360°.
- Goose-style neck allows the lamp to be adjusted in any direction.
- Weighted, steel base prevents tipping.
- Adjustable height: 48" - 72".
- 3-prong plug.
- UL listed.
- For use with incandescent light bulbs up to 60 watts.



**First Aid Box:**

Model NO.B013  
MaterialAluminum + MDF  
UsagePillbox, First Aid Box, Medicine and Drugs Box etc  
TypeBox  
SizeSmall  
WaterproofWaterproof  
HardnessPartial Hard  
Inside MaterialMDF  
Unit N.W.1.76 Kgs  
Magnetic Door  
Yes at The Corner of The Door  
ApplicationSchools, Factories, Hospitals, Hotels, Banks, etc.  
TrademarkGlosen or customized logo  
Transport PackageBrown Box & Master Carton Box  
Specification350x140x420 mm  
OriginChina  
HS Code7616999000



**Microscope**

Model NO.XSZ-107  
 Principle of Optics Biological Microscope  
 Trademark HEB  
 Transport Package Wooden Box  
 Origin Shaanxi, China  
 HS Code 9011800090

XSZ-107 Series Binocular Biological Microscope

XSZ-107 Series Biological microscope has stable frame and can fit monocular, binocular, trinocular head on it. Double layer mechanical stage with adjustable long handle and coaxial coarse /fine focus knob make the operation easily. It is provided with high quality achromatic objectives, wide field eyepieces and halogen lamp adjustable brightness, which guarantee the best image. Also you can equip with phase device. It's both excellent in performance and moderate price. It is used widely for clinical examination, teaching demonstration & cystoscopy in colleges and universities, medical and health establishments, research institutes and department for forestry and agriculture.

Structure: XSZ-107 Series of microscope is composed by nine main component parts:

1. Stand: It's the base bearing total weight of microscope, which builds in illumination system, electronic parts and connecting control.
2. Arm: It's the central part connecting the frame and every main component parts. It's provided with coaxial coarse/fine focus system, with tension adjustable knob and limited stopper.
3. Rise and fall support: It connects with stage, arm and condenser. Stage and condenser can move smoothly through it.
4. Eyepiece head: It can adjust interpupillary distance and visibility, and 45 inclined (Sliding style) or 30 inclined (Compensation free), in order to observe comfortably and conveniently, Binocular head, trinocular head & monocular head are optional.
5. Eyepiece: Using WF10X and WF16X (for choice) wide field eyepiece.
6. Nosepiece: It guarantees smooth rotation by quadruple revolving nosepiece.



**Square Plate**



Model NO.TJ-016  
Product Size20\*13\*3  
NamePlate  
SterilizationYes  
UseOral Surgery  
Net Weight1.8kg  
Packages Size25\*16\*6  
Use TimeNon-Diaposable  
Size12, 10, 9, 8  
MaterialsStainless Steel  
TrademarkTJDent  
Transport PackageCarton Box  
Specification0.8kg  
OriginChina  
HS Code901849900

**Features:**

.Made of medical grade stainless steel.Can be sterilized.

Affordable price with superior quality.

Sterilization name	can be Sterilized square plate
Gross Weight	0.8kg
Product Size	20*13*3





Steps



Model NO.BT358-2  
Trademarkbetter medical  
OriginChina  
HS Code9506911900  
Size 510\*460\*350mm  
Material #304 stainless steel







## Medical Stool with Back



Providing long-lasting furniture Gurantee

\*General Use: Office Furniture, Commercial Furniture, Home Furniture

Model NO.HS-018-back

ColorMore Color

Transport PackageCarton

OriginZhejiang Huzhou

Product Size 48\*48\*68-84cm

Packing Size 56\*56\*78cm

G.W 4.3kgs/ctn

Base Nylon base



It is the perfect chair to conduct the medical examination. He has mounted wheels that allow for easy and efficient movement of chairs. It has backrest, which increases comfort. It is height-adjustable.

\*Contemporary design, simple facade



**Medical Bed 3 Funcions(Electric)**



Model NO.AG-BM104  
 Model NumberAG-Bm104  
 Size2130\*970\*540mm  
 CertificatesISO, CE  
 TrademarkAegean  
 Transport PackageWooden Case  
 SpecificationCE&ISO  
 OriginJiangsu  
 HS Code94029000

Model: AG-BM104

**Features:**

- 1)Durable frame: Made of cold-rolled steel plate and tube, electro-coating & powder-coating treatment;
  - 2)Detchable al-alloy tube plus plastic board headboard/footboard;
  - 3)4-part Steel bed board;
  - 4)4-crank al-alloy rails with foldable dining table;
  - 5)Ordinary wheels, φ 125mm with cross brakes.
- Fully tested sturdy construction capable of taking a maximum user weight of up to 250kg.

Product name: 3 functions electric hospital bed

Product Model: XF833

**Specification**

Overall Size L2120×W970×H500-750mm

Sleeping platform size L1950\*W840mm

Load capacity hold 250kgs working load(static),160kgs working load(dynamic)

**Functions**

- 1)Back section adjustable from 0°to 80°± 5°(by linear actuator)
- 2)Knee section adjustable from 0°to 40°± 5°(by linear actuator)
- 3)HI-LOW adjustable from 500 to 750mm (by linear actuator)



## Medical Bed 5 Funcions(Electric)



1. Size: L 2120 mm x W 970 mm x H (500 mm – 700 mm)
2. Material: Cold rolled carbon steel, ABS, Stainless steel
3. Metal Type: Powder Coated Steel
4. Type: Hospital Furniture
5. Specific Use: Intensive Care Unit.

### Electric Hospital Bed Manufacturer With CE Certification

Most five-function electric hospital beds are used in hospital intensive care units. Because this bed can adjust the height, tilting back and forth. These features can be used to meet the needs of patients for postoperative recovery. Satcon Medical is a professional hospital bed manufacturer, distributor and solution provider.

Our company has participated in the bidding and procurement of many overseas hospitals. We have rich experience in controlling risks in international trade process, documents required in tender process and quality control of goods.

### Electric Hospital Bed ST-EH01 Product Description

1. The headboard and guardrail are integrally injection molded with ABS, which is beautiful and durable.
2. This bed is equipped with a 125 mm PU double-sided silent wheel for smooth operation and easy operation.
3. The bed surface is formed by one-time stamping of 1.2 mm cold-rolled steel plate, ultrasonic rust removal, strong impact resistance and corrosion resistance.
4. Trendelenburg Position & Rev. Trendelenburg Position: 0° – 12°
5. The motor of the bed adopts the internationally renowned brand Lincoln Motor and has passed the ROHS certification.

### Medical Bed ST-EH01 Product Parameters

## Suction Machine 2 Bottles



Model NO.7A-23D  
 Certificate ISO  
 Max Negative Pressure  $\geq 0.09$ MPa  
 Noise  $\leq 65$  dB (a)  
 Power  $\leq 180$ va  
 Pumping Rate  $\geq 20$ L/Min  
 Reservoir Capacity 2500ml/PC, 2pieces  
 Origin Jiangsu, China

7A-23D Electric suction apparatus adopts completely plastic panel design which makes it more fancy and fashionable. The device of intercepting oil for circumfluence can reduce the oil pollution. Easy to carry, low noise, high negative pressure and large flux. It can be widely applied in the surgical operations which need to absorb phlegm, thick liquids etc.

### **Features:**

Adopting oil-free piston pump  
 Clean-without pollution of oil and smoke  
 Convent-no need add oil to maintain daily  
 Safe-no plus pressure during using  
 No flow backwards pressure when the machine stops,so the liquid won't flow backwards  
 Complete plastic panels, hand-switch and foot-switch for operating easily. Select negative pressure at will with no level for pressure adjustment, and overflow protection mechanism, safe and reliable.

### **Principle technical data:**

Max negative pressure:  $\geq 0.09$ MPa  
 Noise:  $\leq 65$  dB (A)  
 Power:  $\leq 180$ VA  
 Pumping rate:  $\geq 20$ L/min  
 Reservoir capacity: 2500mL/pc, 2pieces



**Digital Sphygmanometer**

Brand	Yuwell
Model	YE-680A
Operation	Automatic
Measurement Point	ARM
Made By	Germany
Color	Regular
Warranty	NA
Displaying	: LCD digital display
Measuring method	: oscillation mensuration
Measuring range	: Systolic pressure: 60-230mmHg(8.0-30.7kPa)
	: Diastolic pressure: 40-130mmHg(5.3-17.3kPa)
	: Pulse rate: 40-200times/min
	: Precision: pressure: within $\pm 3$ mmHg
	: Pulse rate: within 5% of reading value
	: Working system: Intermittent operation
Features:	
	- Large-scale LCD - 360° testing cuff
	- Intergrated air plug design
	- Cuff wrapping detection
	- IHB indication
	- Body movement detection
	- 60 groups of memory(YE650A)
	- Average value display of three times measurement

## Air Mattress



The mattress are designed to match with pump air output input cycle and formation makes air channel up and down in every 5 minutes to makes air can go through patient back to release pressure sore occur. As this idea, the mattress effective match with air pump operate can reduces the workload for the caregiver and provide patient more comfortable, helping to prevent heal bedsores.

The micro air holes can via air loss to provide patient more dry environment to prevent patient back due to long term lying on the bed an sweat can evaporation caused the bed soared occur BUBBLE MATTRESS SYSTEM.

It is an economical type and be directly used on the hospital bed or nursing home, also easy user to put bubble mattress on the other mattress.

Material: PVC (EN-71, non-toxic)

Thickness: 0.35mm

Size (inflated): 78\*34

Air output: 4~6L/min.

Cycle time: 5 min.

Supply voltage: 220V/110V

Pressure range: 110~140mmHg

Ball height (inflated): 21/2

Number of cells (inflated): 130

Power Line Length: 1.8m

Origin: China



**Centerifuge 80-1****Model No.****80-1****Laboratory centrifuge**

800 Series electric centrifuge is widely used in hospitals, chemical and Biological Chemistry Laboratory for serum, plasma, immune qualitative analysis experiment. Has beautiful shape, large capacity, small volume, complete function. Its performance is stable, the speed is adjustable and can automatically adjust the balance, low temperature, high efficiency and wide applicability and advantages.

**Specifications of 80-1 Tabletop Low speed Centrifuge**

Power Supply	AC 220V/110V 50Hz/60Hz
Max speed	4000rpm
Capactiy	20ml*6(angle rotor of 45degree)
Max rcf	1790xg
Timer	0-60min
Overall size	275× 245× 235mm
Motor power	40W



**Examination Bed**

- leather:Flame retardant, yellow resistance, mildew resistance, bending resistance, 100,000 times wear resistance
- \* Sponge:Flame retardant, 4 cm thickness, high-density foam, density 30 kg/m<sup>3</sup>
- \* Painting:11 Process epoxy painting, ASTM testing anti-bacterial, paint thickness 0.12mm, brightness 60°, paint can resist 50kg impact
- \* Metal Material:Baosteel from Fortune Global 500
- \* Panasonic Robotic ensure 360° full smooth wedding
- \* 4 pcs Anti-slip bed feet covers
- \* 1.2-1.5 mm Thickness powder coated steel frame,250 kg bear loading

**Examination Couch Description:**

- 1.The frame of this couch is made of power coated steel, white color.
- 2.The surface is equipped with soft sponge mattress, PU cover, waterproof, easy cleaning, wear- resisting.
- 3.Water proof and washable mattress.Epoxy coated bed frame.Back section up and down by manual way.

**Advantage:**

- 1.Good product quality
- 2.Product quality assurance for two years
- 3.Manufacturer directly supplies products





**Digital Baby Scale**

Model	EBSA-20
Capacity	20kg/5g
Units	kg/lb
Item material	ABS
Scale size	54.5*33*14.5cm
Power supply	4*AA batteries
Function	Auto power off / Tare,Low Power indication
Carton size	73*59*38cm/4pcs/20.5kg
Work temperature:	10 ~ 40 LED display
Environmental humidity:	<80%
Max. capacity:	20kg
Graduation:	5g
Power supply:	4 sections of high quality dry cell
Low power:	L o o
Error of indication:	Erro
Unit change:	kg or lb
Memory function:	optionally save and recall weighing value
Turn off automatically	
Dimensions:	54.5*33*14.5cm
PACKING(1PCS/CTN)	55.2*33*15cm
Qty/20container	1050pcs
Use 4*AA Batteries	(not included)
LED display	

**Patient Trolley**



Stainless steel patient transferring trolley

1. CE&ISO certified patient transporting trolley
2. Stainless steel structure
3. Artificial leather cover mattress surface
4. Crossed braking system
5. 2pcs S.S. Side rails

Overall size (L*W*H)	1860*590*700mm
Silent wheels and two crossed with brakes	Dia 125mm(5")
Loading capacity	175kgs
S.S. side rails	2pcs, collapsible
Packing	Carton or wooden case
Side rails	2 pcs, stainless steel material, anti-bacteria
I. V pole	1 pc
I. V pole sockets	4 pcs
Wheels	4 pcs
Mattress surface board	1 set (PP material)

Standard Configurations:

- 1) Stretchers can be moved.
- 2) With infusion rack, guardrail, 125 casters.

**Description:**

Stainless steel structure  
 Patient surface: Foam mattress with artificial leather cover  
 Side rails: 2pcs, S.S. material, foldable  
 Four 125mm castors and two crossed with brakes  
 With I.V. Pole and I.V. sockets



## Nebulizer home use



Product: Nebulizer Machine  
Brand: Yuwell  
Model: 403 AI  
Origin: China  
PRICE: 2980/-

### **Features:**

- High performance.
- Rapid nebulization.
- Durable construction.
- Maximum pressure: 2.5 bar.
- Airflow: 10 L / min.
- Weight: 2 kg.
- Dimensions: 34 x 19 x 12 cm

- Professional Medical Grade
- Nebulizer Fine Particles
- Low Noise
- Oil-Free Piston Pump
- Small Round Slee



**Yuwell Wheel Chair**



Alum,frame,powder coated surface, detachable armrest,swing away footrest,8" front castor,24"rear wheel,comfortable-height armrest,back reclining angle also adjustable, double detachable cushion and back pad.

Frame	Steel
Cross Bar	Single
Front Fork	Steel
Finish	Powder Coated
Foot Plate Material	Plastic
Rear Wheel	24"
Tyre	solid rubber
Front Wheel	8"*1 rubber
Armrest	Detachable
Armrest Material	PVC
Side Board	Plastic
Back	Foldable
Cusion Material	canvas
Leg	swing-away
Anti-Tipper	optional
N.W(kg)	19.6
G.W(kg)	22.6
Dimension(mm)	70*30*79
Capacity(kg)	110

## Yuwell Sphygmanometer



Model NO.Type A  
G.W.18.8kg  
TrademarkYUWELL  
Transport PackageExport Package  
Specification370\*160\*85  
OriginChina

### Product Description

Name:Mercury sphygmomanometer

Packing:In box in English

Package included:1 set sphygmomanometer(with English instructions)

Function :

Accurate measurement: measure your blood pressure data accurately;

Durable comfort: Corrosion resistant, wearable and non deformation;

Simple and easy to use: Everyone can use it and care about family health;

High quality and good products: For the health of you and your family,please be ever prepared

Mercury blood pressure meter Pressure Detection range : 0kPa-40kPa (0-300mmHg)

Pulse frequency Detection range 40 times/min-150 times/min;

Cuff range: 22-32CM

**9-eyes Operation Lamp LED**



Perfect Cold Light Effect  
 Perfect green light source new LED green light source, no radiation, no ultraviolet, no infrared, no radiation and low energy consumption, little temperature rise and perfect sunlight like shadowless effect  
 Deep Lighting and Perfect Shadowless Effect  
 Arc focus design generating a great shadowless effect and deep lighting effect, Ingenious escape the doctor's head and arm block

Model No.: CreLed 5700  
 Type: Operating Light  
 Kind: Orthopedics  
 Certification: ISO13485, FDA, SGS, CE  
 Group: Adult  
 LCD Display: With LCD Display  
 Source: Air  
 Anesthesia: Closed Circuit  
 Type of Operating Light: Single Operating Light  
 Lighting Depth: 1200mm  
 Ra: 96  
 Illumination: 160 000 Lux

The white LED has a feature of color temperature which is different from the light source of common shadowless lamps for operation. It may enhance the chromatic aberration between blood, other body tissues and organs, and it thus helps the operating doctor to have a clearer view.  
 Long Service Life-span  
 Perfect green light source new LED green light source, bulb service life-span over 50000 hours  
 Ideal Purification Requirements of Shape Design  
 Cruciform design of the lamp shape, allow the light to bypass the surgeon's head and shoulder block, reduce light source, achieve real shadowless effect. Compared with the traditional circular lamp, the block size was reduced by 30%, improved purification effect, meet the demanding requirements of clean operation room